







# VOLTAGE TRANSFORMERS

**600 VOLT  
CLASS**

Application Data			4
MODEL NUMBER	ACCURACY CLASS THERMAL RATING	OVERALL SIZE Width Height Depth	PAGE
Single Phase			
467	± 1% @ 5VA 40VA @ 30° C.	3.00 x 3.63 x 3.50	5
468	± 0.6% @ 7.5VA 75VA @ 30° C.	3.63 x 4.06 x 2.81	6
465	0.6W & 1.2X 150VA @ 30° C.	3.63 x 4.25 x 3.75	7
460	0.6W & 1.2X 150VA @ 30° C.	4.50 x 3.88 x 4.75	8
460 F & FF	0.6W & 1.2X 150VA @ 30° C.	4.57 x 4.75 x 4.32	9
475	0.3W, 0.6X & 1.2M 300VA @ 30° C.	4.38 x 4.63 x 4.75	10

# VOLTAGE TRANSFORMERS

**600 VOLT  
CLASS**

MODEL NUMBER	ACCURACY CLASS THERMAL RATING	OVERALL SIZE			PAGE
		Width	Height	Depth	
<b>Single Phase</b>					
<b>456, F &amp; FF</b>	0.3W, X, M & 0.6Y 500VA @ 30°C.	6.00	6.10	6.50	<b>11</b>
					
<b>450, F &amp; FF</b>	0.3W, X, M, Y & 1.2Z 750VA @ 30°C.	6.00	6.10	6.50	<b>12</b>
					
<b>Three Phase</b>					
<b>2VT469</b>	± 1% @ 5VA 40VA Per phase @ 30°C.	4.19	3.63	4.38	<b>13</b>
					
<b>3VT471</b>	± 1% @ 5VA 40VA Per phase @ 30°C.	4.59	5.57	3.00	<b>14</b>
					
<b>3VT472</b>	± 1% @ 5VA 40VA Per phase @ 30°C.	5.00	4.13	4.38	<b>15</b>
					
<b>3VT468</b>	± 0.6% @ 7.5VA 75VA @ 30°C. Per phase	7.68	5.38	3.75	<b>16</b>
					

# VOLTAGE TRANSFORMERS

**600 VOLT  
CLASS**

MODEL NUMBER	ACCURACY CLASS THERMAL RATING	OVERALL SIZE Width Height Depth	PAGE
<b>Three Phase</b>			
<b>2VT460</b>	0.6W & 1.2X Per Phase 150VA Per phase @ 30°C.	7.68 x 5.38 x 3.75	<b>17</b>
<b>3VTN460</b>	0.6W & 1.2X Per Phase 150VA Per phase @ 30°C. LINE TO NEUTRAL CONNECTION	10.25 x 4.75 x 4.75	<b>18</b>
<b>3VTL460</b>	0.6W & 1.2X Per Phase 150VA Per phase @ 30°C. LINE TO LINE CONNECTION	10.25 x 4.75 x 4.75	<b>19</b>
CIRCLE DIAGRAM METHODS FOR THE ESTIMATION OF VOLTAGE TRANSFORMER ACCURACY CLASSES			<b>20 &amp; 21</b>